

SADLAK INDUSTRIES LLC

Nadeau Industrial Park • 712 Bread & Milk St. Unit 7 • P.O. Box 202 Coventry, CT 06238
Tel. (860) 742-0227 • Fax. (860) 742-4244 • Email sales@sadlak.com • Website www.sadlak.com

IF YOU ARE HAVING INSTALLATION PROBLEMS

After the initial scope mount installation, if you are having a problem of being off center, running out of adjustment, etc, please try to re-install the mount.

Start with the cam washer tab at 9 o'clock.

With hex screw finger tight (very light) push mount forward until it contacts the underside lobe on the cam washer.

Now push the front of the rail down with light pressure (the rear should rise slightly).

Next tap the tab CW - tab will go to about 10 o'clock and hex screw will tighten at same time. Back off hex screw slightly and tap again. Each time you tap the tab, the mount will move back toward the angle face.

Repeat as many time needed until the mount just touches the stripper clip guide angle face.

Insert stripper clip guide - just to make sure it will slid in. If not try tapping tab more to ride mount a little more up the angle face. Remember to always have the hex screw snug during the tapping procedure.

Once stripper clip guide slides in easy and the middle socket screw will start to thread in, tighten the hex screw to 65 in-lbs

Now final torque the middle soc screw into the stripper clip guide to about 35 in-lbs.

Set the front set screw per original instructions

Bring to range and test it out.

Thanks for your patience

Dee Dickson